



Infrared Classroom Audio System

Models PA-IRSYSB (Four Speaker System)
PA-IRSYS (Two Speaker System)

Califone understands that the proper utilization of audio technology can assist classroom learning and student comprehension.

Acknowledged research has validated the use of enhanced sound field amplification in learning areas. The Infrared Classroom Audio System delivers all of the benefits of sound field amplification with greater audio coverage & reception with dual ceiling sensors to expand the coverage area and avoids “drop out” of the signals.

The Califone Infrared Classroom Audio Systems will help:

- **Improve academic achievement**
- **Increase on-task behavior**
- **Increase attention to verbal instruction**
- **Improve comprehension for English Language Learners**
- **Improve ease of listening and teaching**
- **Reduce vocal strain and fatigue on teachers**
- **Works with PC/MAC teleconferencing systems such as Microsoft® Netmeeting so the entire class can participate in distance learning applications**

The benefits of the Infrared Classroom Audio System are enhanced by its use of “array” speakers. Array speakers are most commonly seen at concerts and they deliver several advantages of being used in the classroom:

- **Array speakers target a tighter sound pattern directly at the audience with a narrower projection pattern. (A wider pattern bounces the sound off the walls and windows, which adds additional disruptive background noise to the very environment the system was installed to overcome.)**
- **Array speakers distribute the sound more evenly so the volume levels are the same at the front & rear of the room.**



PA-IRSYS shown

“We know that this technology is helping our students. We know they are able to hear the teacher better, which creates a more language-focused learning environment.”

Debra Drysdale, Principal
G.W. Carver Elementary School
Yuma, AZ

“We believe that using the Califone audio system in the classroom helps to naturalize the teacher’s speaking voice, allowing for the appropriate tone and pitch to reach each student. With this system, teachers tend to speak at a lower volume into the microphone, allowing a wider range of pitches to come through, and ultimately this helps to reduce strain on their voices”

Jim Dieckmann, Library Media Teacher, in a Case Study on
Clear View Charter Elementary School
Chula Vista, CA

Califone® International Inc. 800-722-0500
califone.com



Infrared Classroom Audio System

Models **PA-IRSYB** (Four Speaker System)

PA-IRSYS (Two Speaker System)

Features

1. Two ceiling-mounted IR receivers (twice as many as other brands offer as standard equipment) deliver twice the reception with less signal drop out and allows increased wireless coverage within classrooms of up to 2,000 sq. ft.
2. Beltpack transmitter & headset mic* will operate all day long on a single charge. Ensures full wireless mobility to move about the classroom with its 40' transmission range
3. Quick operating guide printed onto the inside of the cabinet for easy referral. Lockable metal case safely stores equipment while not in use
4. Lockable metal case safely stores equipment while not in use
5. Two non-powered array speakers (PI30-SP) with protective steel grilles include wall-mounting brackets and hardware (not shown)
6. All array speakers feature three transducers with high-performance neodymium magnets, which are twice as efficient as conventional ferrite magnets, and deliver more power from a smaller, lighter speaker (which is also easier to install)
7. Built in charging station for the wireless handheld mic. Includes a 2nd infrared frequency enabling both mics to function at the same time
8. Two powered array speakers (PI30-PS with PA-IRSYB package only) comes with fixed and variable volume controls, for other daisy-chained speakers and one for a dedicated speaker system for students with special needs
9. Built-in mixing panel on the front with separate volume levels for both wireless mics, bass, treble controls, IR receiver, and an overnight recharger for the belt-pack transmitter
10. Balanced and unbalanced (3.5mm, XLR, 1/4") mic inputs and aux-in connects the audio from a computer, LCD projectors, and other media players for enhanced audio amplification
11. Designed to specifically connect with PC/MAC teleconference systems such as Microsoft® Netmeeting, enables the entire class to participate in conference calls
12. Exterior flange for surface or flush-mounting the panel box



* Batteries for mics must be purchased separately

Distributed by:

Califone® International Inc. 800-722-0500
califone.com



Infrared Classroom Audio System

Models PA-IRSYB (Four Speaker System)

PA-IRSYS (Two Speaker System)

Specifications

Infrared Mic Specifications*

Transmitting & Receiving Mode IR
 Transmitting & Receiving Frequency 2.35MHz
 Wireless Transmission Range: Approximately 40 ft., for rooms up to 2,000 sq. feet
 240mA
 Current Consumption
 AF Output 650mV AF 1kHz
 Mic Inputs: Balanced and unbalanced, condenser (XLR, 1/4", 3.5mm)
 Line Output: 1/4"
 AC Power Requirements: 110 – 125 VAC, 50/60 Hz
 Modulation: FM (Frequency Modulation)
 Sensitivity: 7 microvolts
 Frequency Response: 50 Hz - 15 KHz +/- 3dB
 Wireless Transmission Range: Approximately 40 ft.
 Dynamic Range: 100 dB
 Distortion <1%
 Battery Two 1.2V (AA) or Two 1.5V (not included)

Student Hand Held Microphone*

Sub-carrier frequencies 2.35MHz
 Microphone Unidirectional, dynamic
 Power 2-'AA' NiMH Rechargeable batteries (not included)
 Microphone Recharging Station Included

"Project Intercept"

Please contact us immediately if you experience any difficulties with your Infrared Classroom Audio System. Our "Project Intercept" customer service program will quickly repair or replace items under warranty. Simply contact us via phone or email warranty@califone.com

Visit our website at www.califone.com to learn more about the complete line of *Califone*® audio enhancing and visual technology products including: Wired and Wireless public address systems and lecterns, wireless microphones, headphones & headsets, group listening centers, multimedia players and computer peripheral products.

We are proud of helping teachers enhance student understanding and achievements since 1947, with your satisfaction as our first priority.

The Infrared Classroom Audio System carries a limited six-year warranty and service support available through authorized dealers nation-wide. Its warranty covers school use - unlike some other PA products whose warranties would be voided if used in schools.

Distributed by:

Receiver/Amplifier

Audio Power 30 Watts RMS
 Power Requirements 18VAC 50 VA
 Speaker Connections for 2 speakers
 Mono inputs 2 - (RCA type, Hi Z, Mixed)
 Auxiliary Volume Control 1
 Sub-carrier frequencies 2.35 MHz or 2.85 MHz
 Type Super heterodyne - crystal controlled
 Signal-to-noise >80 dB
 Image rejection 40 dB
 Reception sensitivity >25dBuV
 Reception selectivity ±40kHz
 Condenser, balanced and unbalanced (3.5mm, XLR, 1/4") mic inputs, aux in and line out

Belt-Pack Transmitter with hands-free headset mic (HBM-316)

Single carrier 2.35MHz
 Audio distortion <1.0%
 Mic input impedance 2.2k ohms
 Auxiliary Mic input jack 3.5mm
 Built-in mic unidirectional electret
 Microphone gain adjustment Max to -50dB
 Power 2-'AA' NiMH rechargeable batteries (not included)

Powered Speakers (two PI30-PS speakers come with PA-IRSYB package only)

Two (2) wall mounted speakers w/ 2 heavy duty steel mounting brackets
 Dual line in Connects audio from whiteboards, LCD projectors, computers, cameras and other media players
 Fixed and Variable Line out Controls the volume to two different sets of speakers

Non-Powered Speakers (PI30-SP)

Two (2) wall mounted speakers w/ 2 heavy duty steel mounting brackets
 Transducers Three per speaker, each 16 Ohm
 Magnets High performance neodymium
 Power rating 30 watts RMS, 150 - 15kHz
 Speaker Weight 3.2 lbs. each, bracket 1.7 lbs each
 Connection Terminals Spring-loaded terminals

External Infrared Dome Sensors

Two (2) 360 degree ceiling mounted infrared sensors for optimal coverage of infrared signal pickup throughout the entire classroom
 Cable length 30 ft standard
 Power Powered by receiver
 Size 3.9" (D) x 1.2" (thick)
 Weight 7.5 oz each
 Sensor Type Lensed infrared diode
 Number of Lensed Diodes 6
 Reception Angle 360 degrees

Storage Cabinet

Construction Lockable steel case stores mics
 Built-in charging ports For belt-pack transmitter & handheld mic
 Dimensions (L x W x H) 10.6" x 4.75" x 11.8"

Total System Weights : PA-IRSYS: ship weight 39 lbs., 1 carton
 PA-IRSYB: ship weight 45 lbs., 2 cartons

Safety Approvals: AC Wall adapter is C-UL/CE approved
 Warranty 6 years from date of purchase (PA only, all other parts one year)