



# Model PA329 | Wireless PresentationPro™



Includes magnetic volume/mute remote



Portable or installed, solo or used with other speakers, the PA329 is the ideal wired or wireless voice and audio amplification solution for any presenter. Projecting rich and big sound, the PA329 is one of the most specified speakers by schools and districts because of its power and durability. It has multiple inputs for voice and audio amplification from computers, mobile devices, microphones and other sources.

## PA329 Features

- Rugged steel-reinforced handle for easy mobility
- Volume up / Mute / Volume down controls
- Volume indicator
- Power switch, LED indicator & DC power input jack
- PI-RC Remote controls volume up / down, mute, speaker power and magnetically rests on top of speaker when not in use
- Separate bass, treble controls for quality sound
- 1/4" Line in and line out connect with LCD projectors, computers, whiteboards
- RCA & 3.5mm Aux in jacks connects with mobile devices
- XLR and 1/4" mic inputs
- LED displays wireless mic channel, RF & audio signals, with channel up/down adjustments
- Set button to sync wireless channel with transmitting mic
- Microphone volume control
- Ideal for mobile presenters, classroom & athletic uses
- Includes volume/mute remote control

## Specifications

<i>Rated Power Output:</i>	30 watts RMS
<i>Sensitivity for Rated Output: Line:</i>	125 mVrms
<i>Microphone:</i>	4 mVrms
<i>Auxiliary:</i>	250 mVrms
<i>Frequency Response:</i>	60 Hz - 20 kHz ± 3dB
<i>Dispersion Angle:</i>	90° H x 120° V
<i>Speaker:</i>	6.5" full-range speaker
<i>Distortion:</i>	1% (at 10W)
<i>Crossover:</i>	L/C - 6dB/Octave @ 4 kHz
<b>Inputs</b>	
<i>Line inputs:</i>	Hi-Z, RCA (summing L+R)
<i>Balanced mic:</i>	Hi or Lo-Z, with phantom power: (+15 volts D.C.)
<i>Unbalanced mic:</i>	Lo -Z, 1/4"-phone
<i>Aux In:</i>	Hi-Z Mono 1/4"-phone & 3.5mm stereo jack
<b>UHF Receiver Specifications</b>	
<i>Carrier Frequencies:</i>	904 - 925 mHz
<i>Channels:</i>	#1 904.85, #2 905.75, #3 906.85, #4 908.15, #5 909.65, #6 911.35, #7 913.45, #8 914.85, #9 915.75, #10 916.85, #11 918.15, #12 919.65, #13 921.35, #14 923.25, #15 924.15, #16 925.3
<i>Line Output:</i>	250mv constant
<i>Remote Control:</i>	20' range with 45 degree operating field in front of the speaker
<i>AC Power Requirements:</i>	110 - 125 VAC, 50/60 Hz or 208 - 240 VAC, 50/60 Hz
<i>Dimensions:</i>	(HWD): 6.25" x 10" x 8.5"
<i>Weight:</i>	10 pounds, shipping weight 13 lbs.
<i>Warranty:</i>	6 year from date of purchase for use in school, business, church and government facilities