



16 Channel Wireless Transmitter

Model TR-16

1. 150 foot wireless transmission range for venue flexibility and delivery of the presentation
2. Balanced XLR and unbalanced mic inputs (on rear)
3. Stereo Auxiliary Inputs on RCA connectors (on rear)
4. 3.5mm and 1/4" headphone outputs with separate level controls
5. Microphone, auxiliary and earphone volume level adjustments
6. LED level metering
7. 16 channels of selectable UHF
 - Converts audio output from any media player to wireless
 - One year warranty for school use - unlike items purchased from consumer electronics stores whose warranties would be voided if used in schools



The Wireless Transmitter provides cost-effective wireless UHF connectivity for microphones, multimedia players and even computers. It seamlessly integrates with the Califone Wireless PresentationPro (PA300+UHF) and PowerPro (PA916) loudspeaker systems.

"Project Intercept"

Please contact us immediately if you experience any difficulties with your Transmitter. Our "Project Intercept" customer service program will quickly repair or replace items under warranty. Simply contact us via phone or email rilane@califone.com.

Visit our website at www.califone.com to learn more about the complete line of wired and wireless *Califone*® headphones and other audio products including: Public address systems, wireless microphone systems, group listening centers, multimedia players and computer peripheral products.

We are proud of helping teachers enhance student understanding and achievements since 1947, with your satisfaction as our first priority.

This Wireless Transmitter carries a one year warranty and service support available through authorized dealers nationwide.

Distributed by:

Specifications

Oscillation type	PLL synthesized
Adjustable frequencies	16 Selectable UHF frequencies
Carrier frequency	747 ~ 801.8 MHz, FM emission
Type of emission	FM
Max modulation	Max ± 50 kHz
RF Carrier power	Hi: 50mW /Lo: 10mW
Compander system	Compander and ALC
Frequency response	100 Hz ~ 15 kHz
T.H.D	< 1 %
Dynamic range	100 dB
Tone frequency	38 kHz
Power requirement	AC adaptor 12V, 0.5A
Input / Output	mic, aux / ear phone
Controls volume	Aux/vol, mic/vol, ear phone/vol
Dimensions	21.5L x 20W x 5H cm
Weight	3 pounds shipping weight
Product Compatibility	Transmits to the Califone wireless PresentationPro (PA300+UHF) PowerPro (PA916) and the PowerPro wireless companion speaker (PA916-PS) Wireless Receiver (R-16) connects with any existing wired PA system
Safety Listings	C-UL & CE approved for use in schools, churches, business and gov't facilities
Warranty	1 year warranty from date of purchase

Califone® International Inc. 800-722-0500
www.califone.com